

LISTING OF THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the present application. Additions are identified by underlining. Deletions are indicated by ~~strike through~~ or [brackets].

1. (Original) A method of operating a communications network including a firewall comprising the steps of:

monitoring delays associated with the closing of ports corresponding to communications sessions following the termination of said communications sessions as indicated by session control signals; and

generating an alert signal when a monitored closing delay exceeds a preselected threshold.

2. (Original) The method according to claim 1, further comprising the steps of: communicating said alert signal to a security management system; and operating said security management system to initiate at least one security operation in response to said alert signal.

3. (Original) The method of claim 2, wherein said step of initiating at least one security operation includes:

adjusting network routing to reduce the load on the firewall system which triggered said alarm signal.

4. (Original) The method of claim 2, wherein said step of initiating at least one security operation includes:

controlling the firewall at which said closing delay exceeding said threshold was detected to drop traffic until the detected closing delays at said firewall no longer exceed said threshold.

5. (Original) The method of claim 2, wherein said step of initiating at least one security operation includes:
notifying a system administrator of said alarm condition.
6. (Original) The method of claim 2, wherein monitoring delays associated with the closing of ports corresponding to communications sessions includes:
transmitting test signals through a port corresponding to an established communications session;
monitoring to detect said test signals which pass through said port;
transmitting a signal to terminate said established communications session; and
determining the time between transmitting said signal to terminate said established communications session and when the monitored test signals can no longer be detected passing through said port.
7. (Original) The method of claim 6, wherein said test signals are IP packets and where said signal to terminate said established communications session is one of a SIP and an H.323 compliant signals.
8. (Original) The method of claim 7, further comprising: monitoring delays associated with the opening of ports corresponding to communications sessions following the transmission of session initiation signals used to establish said communications session; and
generating an opening delay alert signal when a monitored opening delay exceeds a preselected opening delay threshold.
9. (Currently Amended) A method of operating a communications network including a firewall comprising the steps of:
monitoring delays associated with the opening of ports corresponding to communications sessions being initiated through the use of session control signals; and
generating an alert signal when a monitored opening delay exceeds a preselected threshold.

10. (Original) The method according to claim 9, further comprising the steps of:
communicating said alert signal to a security management system; and
operating said security management system to initiate at least one security operation in
response to said alert signal.
11. (Original) The method of claim 10, wherein said step of initiating at least one
security operation includes:
adjusting network routing to reduce the load on the firewall system which
triggered said alarm signal.
12. (Original) The method of claim 10, wherein said step of initiating at least one
security operation includes:
controlling the firewall at which said opening delay exceeding said threshold was
detected to drop traffic until the detected opening delays at said firewall no longer exceed
said threshold.
13. (Original) The method of claim 10, wherein said step of initiating at least one
security operation includes:
notifying a system administrator of said alarm condition.
14. (Currently Amended) A communications system comprising;
a firewall system responsive to session signals to open and close ports in response
to the establishment and termination of communications sessions, respectively;
means for monitoring said firewall to detect a port closing delay following a
signal to terminate a communications session; and
an alarm generation device for generating an alarm when [a] the port closing
delay is determined to exceed a preselected threshold.
15. (Original) The communications system of claim 14, further comprising:

a security management system for receiving alarms generated by said alarm generation device and for performing at least one security operation in response to said alert signal.

16. (Original) The communications system of claim 15, wherein said at least one security operation is a routing change operation, said security management system including means for transmitting routing change information to at least one network router to redirect at least some communications traffic away from said firewall to thereby reduce the traffic load on said firewall.

17. (Original) The communications system of claim 15, wherein said at least one security operation is a firewall control operation, said security management system including means for signaling said firewall to drop traffic to reduce the load on said firewall.

18. (Original) The communications system of claim 15, wherein said at least one security operation includes notifying a system administrator of said detected port closing delay exceeding said preselected threshold, said security management system including a graphical display for showing a graphical representation of the detected port closing delay information.

19. (Original) The communications system of claim 15, wherein said means for monitoring said firewall to detect a port closing delay following a signal to terminate a communications session includes:

a probe signal generator for generating test signals directed at a port associated with the communications session being terminated; and

a signal analyzer for determining when said generated test signals cease passing through said port associated with the communication session following transmission of a signal to terminate said communications session.

20. (Original) The communications system of claim 19, wherein said probe signal generator includes means for generating session signals used to initiate and terminate communications sessions conducted through said firewall.
21. (Original) The communications system of claim 20, wherein said session signals are one of SIP signals and H.323 signals.
22. (Original) The communications system of claim 20, wherein at least some of said test signals are IP packets.
23. (Original) The communications system of claim 15, wherein said security management system includes:
means for receiving alarms from a plurality of different alarm generation devices located at different locations in said communications system; and
means for analyzing alarms received from different alarm generation devices, over a period of time, to identify the location of one or more traffic sources causing alarms during said period of time.
24. (Original) The communications system of claim 15, wherein said security management system includes:
means for receiving alarms from a plurality of different alarm generation devices located at different locations in said communications system; and
means for analyzing alarms received from different alarm generation devices, over a period of time, to predict the occurrence of future security alarms.
25. (Currently Amended) A communications system comprising;
a firewall system responsive to session signals to open and close ports in response to the establishment and termination of communications sessions, respectively;
means for monitoring said firewall to detect a port opening delay following a signal to establish a communications session; and

an alarm generation device for generating an alarm when [a] the port opening delay is determined to exceed a preselected threshold.

26. (Original) The communications system of claim 14, further comprising:
a security management system for receiving alarms generated by said alarm generation device and for performing at least one security operation in response to said alert signal.